PINNACLE SSL-SL300

EVALUATION/ORDER FORM

Quote	e Order			
Date:		Account Number:		
Sales Representative:		Projected Close Date:		
Dealer Name:		Purchase Order Number:		
Address:		Ship To Address:		
City:	State: Zip:	- 1		
•	Fax:	Contact:	Contact:	
		Phone:		
Shipping Method: Pick up Common Carrier		Opportunity Reference / Project Name:		
PRIMAR	Y MODEL			
QTY:	SSL-SL300: Standard 15'6" rail			
CONFIG	URATION			
QTY:	SL300COS: Standard 15'6" rail with chassis obstruction sensors	QTY:	SSL-SL300FR-LH: Left hand folding rail; 15' 6" rail	
QTY:	SL300-PSPF: Power Swivel + Footrest bundle	QTY:	SSL-SL300FR-RH: Right hand folding rail; 15' 6" rail	
QTY:	SL300-PS: Power Swivel			
QTY	SL300-PF: Power Footrest			
TRACK.	PARTS AND OPTIONS			
TRACK		PARTS ANI	OOPTIONS	
QTY:	SSL-T3-SV: 3' mid-section assembly with brackets	QTY:	SSL-KEY: Key lock on lift (chassis)	
QTY:	SSL-T5-SV: 5' mid-section assembly with brackets	QTY:	SSL-SB1: Additional short brackets	
QTY:	SSL-T8-SV: 7'9" mid-section assembly with brackets	QTY:	SSL-TB1: Additional tall brackets	
QTY:	SSL-8 FT TRACK: 7'-9" track in lieu of standard	QTY:	SSL-CORD-8: 8' charger cord extension	
QTY:	SSL-KNT: No track or brackets in lieu of standard	QTY:	SSL-RET: Retractable seat belt (dealer install)	
SSL-C	C: Custom cut* feet in length (including overrun)	QTY:	SSL-MLT: Manual lowering tool	
* Single unit orders only Must include additional mid-section(s) above if total above		QTY:	SSL-WA: Lock out switch (WA)	
15'6".	e additional mid-section(s) above il total above	QTY:	SSL-EXT: Extension for retractable seatbelt	
HOW TO) MEASURE			
RISE		MEASUREMENTS		
		A to B: Inches from top landing to bottom floor A to H: Inches from top landing to nearest obstruction		
TREA	AD		i.e. a door)	
20.17* A to 5 Total Rail Length		Rise in. Tread in. Stair width in. 7" overrun recommended if top landing is clear (This is added to the A to B) Note: You must order a Tall Bracket if A to H is < 13".		

